

Table top

Capacity (kg)	Accuracy (g)	Platter size (mm)
6	0.5	280 x 348
15	1	280 x 348
30	2	280 x 348

Four loadcell platform scale (distributed and concentrated load)

Capacity (kg)	Accuracy (g)	Platform size (mm)	Loadcell	Frame work	Platter
600/1000/1500/ 2000/3000/5000	50/100/100/ 200/200/500	1000 x 1200 1200 x 1500 1500 x 1800	Tool steel-IP67	MS	MSC
600	50	700 x 800	Tool steel-IP67	MS	MSC

Single loadcell platform scale

Capacity (kg)	Accuracy (g)	Platform size (mm)	Loadcell	Frame work	Platter
30	2	400 x 400	Aluminium	MS	SS
50/150	5/10	450 x 550	Tool steel-IP67	MS	SS-304
150/300	10/20	550 x 650	Tool steel-IP67	MS	SS-304
300/600	20/50	700 x 800	Tool steel-IP67	MS	SS/MSC

Memory	4MB Flash
Number of Keys	55 (Mechanical type)
Interfaces	1 x RS-232 Serial, 1 x Ethernet, 1 x PS/2 port for Keyboard or Scanner Optional : Second platform, 2 Colour Tower Lamp, Buzzer
Display Type	Graphic Dot-matrix LCD with back light
Printing Speed	80 mm/Sec
Label roll diameter (Max)	Outer : 110 mm Inner : 28 mm
Label thickness (Max)	170 microns
Label width & length (Min ~ Max)	25~54 mm, 25~110 mm
Physical dimension	490 mm x 360 mm x 450 mm (Table Top)