

Capacity (kg)	Accuracy (g)	Platform Size (mm)	Frame Work	Platter
3/6/15/30	0.2/0.5/1/2	360 x 276	SS	SS-304
6/15/30	0.5/1/2	400 x 400		SS
6/15/30	0.5/1/2	400 x 400	MS	SS-304
50/150	5/10	450 x 550		SS
150/300	10/20	550 x 650		MSC
300	20	610 x 610		MS
300	50	700 x 800		SS/MS
300	20	700 x 800		
300/600	20/50	700 x 800		
50/60/100/150	5/5/10/10	450 x 550	SS-304/316	SS-304/316
100/150/300	10/10/20	550 x 650		
300/600	20/50	700 x 800	SS-304	SS-304

Capacity (kg)	Accuracy (g)	Platform Size (mm)	Frame Work	Platter
600	50	700 x 800	MS	MSC
500/1000/1500 2000/3000/5000	100/200/200 500/500/1000	1000 x 1200/1200 x 1200 1200 x 1500/1500 x 1500/1500 x 1800		
600/1000/1500	100/200/200	1000 x 1200	SS-304	SS-304

Ramp Size (mm)	MOC	Capacity (kg)
1200 x 1000	MSC/SS-304	600 ~ 3000
1500 x 1000		
1800 x 1000		

Capacity (kg)	Accuracy (g)	Platform Size (mm)
150/300/600	20/50/100	600 x 600
150/300/600	20/50/100	850 x 850
600/1000/1500	100/200/200	1250 x 1250
600/1000/1500	100/200/200	1500 x 1500

Ramp Size (mm)	Capacity (kg)
600 x 230	150 ~ 600
850 x 230	
1250 x 455	600 ~ 1500
1500 x 455	

#### Indicator Specification

##### Standard Interface

RS-232 / RS-485 Modbus RTU

##### Optional Interface

Ethernet / IP

4-20 mA Analog output

DIO (8 In & 12 Out OC)

##### Load cell Specification

Nickel plated alloy steel IP-67 load cell

High reliability

##### Silent Features

Wide choice of Indicator options

PLC Interface protocol

Panel mount Indicator (Aluminium)

Flame proof Indicator

##### Tank Weighing kit Specification

Fully Stainless Steel (SS-304) load cell kit

Model	Capacity (kg)	Accuracy (g)	Load Cell Kit
DI-60	300	100	3 Load Cell
	600	100	
	1500	500	
	3000	1000	
	6000	2000	
	10000	5000	
	300	100	
600	100		
1500	500		
3000	1000		
6000	2000		
	10000	5000	