

<b>Model number</b>	FB-200	FB-300	FB-600	PG-1000
<b>Maximum weighing capacity</b>	200 g	300 g	600 g	1000 g
<b>Readability</b>	0.001 g	0.001 g	0.005 g	0.01 g
<b>Display resolution</b>	2,00,000	3,00,000	1,20,000	1,00,000
<b>Platter Size</b>	Dia 110 mm	Dia 110 mm	Dia 110 mm	Dia 150 mm
<b>Draft Shield</b>	Included (Standard)	Included (Standard)	Included (Standard)	Optional accessory

<b>Model number</b>	FB-600	FB-2000	FB-3000
<b>Maximum weighing capacity</b>	600 g	2000 g	3000 g
<b>Readability</b>	0.001 g	0.01 g	0.01 g
<b>Display resolution</b>	6,00,000	2,00,000	3,00,000
<b>Platter size</b>	Dia 110 mm	Dia 150 mm	Dia 150 mm
<b>Draft shield</b>	Included (Standard)	Optional accessory	Optional accessory

<b>Technology</b>	Electro Magnetic Force Restoration Technology (EMFRT)	<b>Calibration method</b>	Automatic software calibration (External weight)
<b>Operating temperature</b>	+10°C to +40°C	<b>Tare range</b>	Full capacity
<b>Sensitivity drift (20°C to 40°C)</b>	+/- 5 ppm/°C	<b>Repeatability / Verification interval Linearity</b>	+/- 1 d +/- 2 d
<b>Display type</b>	Green Vacuum Fluorescent Display (VFD)	<b>Dimensions without draft shield (Width x Depth x Height)</b>	190 mm x 275 mm x 85 mm (Table-top)
<b>Display digits / Size</b>	7 Digits / 13 mm	<b>Approx. gross weight (balance only)</b>	2 to 2.3 kg (Table-top)
<b>Power supply - AC / DC adaptor</b>	Input – 230 V AC, 50 Hz Output – 6.9 V DC @ 1.5 A Max Watt – 13 W	<b>W&amp;M classification</b>	Class II (PG Series) Class I (FB Series)
<b>Processor</b>	Digital 8-bit micro-computer	<b>Default weighing units</b>	Grams